



PYLOCX Comfort

PL60XX

PL6021 Comfort
25 mm / 30 mm
55 mm / 65 mm
(5 mm)
EURO.



Features

- 25 mm / 30 mm / 55 mm / 65 mm
-
- Euro
- 30°C - + 60°C
-
- PIN
- 10.000
- VdS
- IP65

Additional Information

PYKEY
10.000
IP65

Additional Information



XXXXXXXXXXXXXXXXXXXX

XXXXXXXXXX

XXXXXXXXXXXXXXXXXX

XXXXXX

XXXXXX

XXXXXXXXXX

VdS 2.344:2.014-07 , VdS 2.156-2:2.013-06 , VdS 2.386:2.012-07 , DIN EN

XXXXXX XXXXXXXXXXXXX

15.684:2.013-02

XXXX XXXXXXXXXXXXX XXX XXXXXXX XXXXXXXXXXXXX XXX XXXXXXX Euro

XXXXXX XXXXXXXXXXXXX

IP65

XXXXXXXXXXXXXXXXXX

XX X XXXXXXX XXXXXXX XXX XXXXXXX XXX XXXXXXXXXXXXX XXXXXXXXXXXXX

XXXXXX XXXXXXXXXXXXX

-30°C - + 60°C

XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXX

XXXX XXXXXXXXXXXXX

PYKEY

XXXXXX XXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXX

XXXXXX XXXXXXX

XXXXXXXXXXXXXXXXXX XXXXXXX, XXXXXXXXXXXXXXXXXXX XXXXXXX XXXXXXXXXXXXXXXXXXX XXXXXXX

XXXXXX

XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXX Euro

XXXXXXXXXXXXXXXXXX XXXXXXXXXXXXX

VdS KL. BZ***

XXXXXX XXXXXXX [mm]

XXXXXXXXXXXXXXXXXX (XXXXXXXXXXXXXXXXXX): 25-55 mm, XXXXXXX XXXXXXXXXXXXXXXXXXX

(XXXXXXXXXXXXXXXXXX): 35-65 mm

| SECURITY
| MADE IN GERMANY
| SINCE 1883



| SECURITY
| MADE IN GERMANY
| SINCE 1883

