SECURITY
MADE IN GERMANY
SINCE 1883

[illegible] PYPROTECT [illegible] [illegible]

[illegible]: V85812110

[illegible] [illegible] [illegible] [illegible] USB [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] LF [illegible] HF, [illegible] [illegible] [illegible]. [illegible] [illegible] [illegible] firmware, [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] PYPROTECT [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] – [illegible] [illegible] [illegible] [illegible] [illegible] Plug & Play, [illegible] [illegible] [illegible] [illegible] 60 [illegible] RFID [illegible] [illegible] [illegible] [illegible] [illegible] RS485.



[illegible]

- Plug & Play [illegible] [illegible] [illegible] 60 [illegible] RFID [illegible] [illegible] [illegible] firmware [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] RS485

[illegible] [illegible]

[illegible] [illegible] [illegible] [illegible] USB [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] LF [illegible] HF. [illegible] [illegible] [illegible], [illegible] [illegible] [illegible] [illegible] [illegible]. [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]. [illegible] [illegible], [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] PYPROTECT [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible].

[illegible] [illegible]

[illegible]	ABS UL94-V0, schwarz
[illegible]	CE/RED, FCC, IC, UL listed, TAA compliant, REACH and RoHS-III compliant

SECURITY
MADE IN GERMANY
SINCE 1883

[illegible]

[illegible]	IP22
[illegible]	-25 °C [illegible] +70 °C
[illegible]	USB 4,3 - 5,5 V, RF on: 120 mA
[illegible] LxBxH	8 x 5,6 x 1,8
[illegible] [illegible] [illegible]	3 LED, 1 [illegible]