

Cold room lock with bar handle

Article No.: EASYLOX.XL

With EASYLOX, the STUV engineers have conceived and designed a modular snap-on locking system that can be individually configured. Elegant stainless steel look or classic black? The modular system makes it easy to combine different decorative panels and interior handle variants.



Properties

- Available in two colour variants
- With inside pushbar
- Optional: OEM version with customer logo on the cover plate
- Variable latch, backset adjustable to 10 mm
- Luminescent function of the covering cap on the inside handle (for emergency opening)
- For door thicknesses from 45 to 165 mm
- Operating range from -30°C to +80°C
- Lockable with wafer cylinder, with two keys, individually lockable 1 10 or in a blind version without a cylinder
- Cut outs identical to STUV VARILOX locking system
- Made of particularly robust, durable and resistant materials: stainless steel and glass-fibre reinforced composite materials

Functional description

Open, close, as intuitive and ergonomically designed as a locking system should be. Simply pull or push in the opening direction of the door to trigger the mechanism.

Locations

- Cold room manufacturer
- Refrigerated vehicles



- Refrigerated hardware trade
- Metal/door construction
- Refrigerated door manufacturer

Technical data

Door thickness [mm]	45 to 165
Material	Composite materials
Surface	Coloured
Colour	RAL 9.005
Door version	Right-hand version / left-hand version
Standards	EN 179 tested
Temperature range	-30°C to +80°C
Door thickness	45 to 165
Locking function	Snap
Locking type	Cylinder
Multi-point locking system	No
Door type	Hinged door
Backset [mm]	80













