

ECOFLEX stainless steel cold room corner hinge, up to 100kg load capacity

Article No.: ECOFLEX

The ECOFLEX 3-part stainless steel corner hinge with black covering caps offers optimum solutions for individual requirements thanks to the rising and non rising versions. The intuitive assembly saves time and makes installation easier.



Properties

- Stainless steel, grinded and blasted
- Load capacity of up to 100 kg with two hinges
- For rebated and surface-mounted doors with an offset of 35 mm or more
- Height adjustment
- Hinge pin with double bearing
- Maximum opening angle of 180°
- Quick and easy assembly
- Anti-dismantling protection
- Can be used for right- and left-hand versions
- For indoor and outdoor use
- Available in rising or non-rising
- With additional locking pins

Functional description

With its slim design, the ECOFLEX fits into any door construction. The door is optimally guided thanks to the double bearing. The integrated height adjustment allows subsequent corrections to the installation location.

Locations

- Cold room manufacturer
- Refrigerated vehicles
- Refrigerated hardware trade
- Metal/door construction
- Refrigerated door manufacturer

Technical data

Load capacity [kg]	up to 100
Offset [mm]	from 35
Material	Stainless steel
Surface	Grinded and blasted
Door version	Right-hand version / left-hand version
Adjustability	1D
Opening angle	180°
Door type	Hinged door
Accessories	Shims
Gradient	Yes / No
Load capacity	up to 100
Offset	from 35
Security	Yes

