

ECOFLEX stainless steel corner hinge for cold rooms, load capacity up to 100 kg

Article No.: ECOFLEX

The 3-part stainless steel corner hinge ECOFLEX with black covering caps offers optimal solutions for individual requirements thanks to the rising and non-rising versions. Intuitive assembly saves time and makes installation easy.



Properties

- Stainless steel, grinded and blasted
- Load capacity with two hinges up to 100 kg
- For rebated and surface-mounted doors from 35 mm offset
- Height adjustment
- Hinge pin double bearing
- Maximum opening angle of 180°
- Simple and quick assembly
- Protection against removal
- Can be used for right-hand and left-hand doors
- For indoor and outdoor use
- Available in rising or non-rising versions
- With additional locking pins

Functional description

With its slim design, the ECOFLEX fits any door construction. The double bearing ensures that the door is guided perfectly. The integrated height adjustment allows subsequent corrections to be made at the installation location.

Places of use

- Cold room manufacturer
- Refrigerated vehicles
- Cooling fitting trade
- Metal/door construction
- Refrigerator door manufacturer

Technical specifications

Offset [mm]	from 35
Material	Stainless steel
Surface	Grinded and blasted
Door version	Right-hand version / Left-hand version
Adjustability	1D
Opening angle	180
Door type	Hinged doors
Accessories	Shims
Slope	Yes / No
Safety	Yes
Load capacity [kg]	up to 100

