

## HSL double bit bolt lock

Article No.: HSL 101

---

High-security bolt lock with single-turn bolt throw. In the standard version, the lock has a mechanical external visual indicator on the key-operated side.



### Properties

- Easy operation with HSL double bit key (1-turn)
- Locking can be changed without a change key

### Functional description

The HSL double bit key is inserted into the lock.

The deadbolt is locked with the key by turning it once (180°).

The door can be opened.

The door is closed.

The deadbolt is pre-locked with the key by turning it once (180°).

The door is completely locked.

Changing the keyed action

The lock can be changed to a different keyed action when unlocked (deadbolt locked). This requires a key for the current keyed action and a key for the future keyed action.

The HSL 101 type is designed as a high-security lock for detention room and passage doors. The deadbolt is locked and unlocked with one turn of the key (180° turn). The key can be removed when locked and unlocked.

### Places of use

- Passage door
- Holding room door
- Armoury door

## Technical specifications

Material	Stainless steel
Surface	Matt
Face plate dimension [mm]	280 x 30 x 4
Material forend	Stainless steel
Material deadbolt	Stainless steel
Material lock housing	Stainless steel
Lock mechanism	HSL double bit
Levers	7
Recodability	yes
Weight [kg]	2.3
Lock dimensions [mm]	200 x 22 x 220
external visual indicator	mechanically
Closing operations	500,000
Max. lateral bolt load capacity [kN]	50



## Technical specifications

Relative humidity [%]	95% non-condensing
-----------------------	--------------------

bolt throw mm	20
---------------	----