

## HSL double bit food hatch lock with latch bolt

Article No.: HSL 201

---

Latchbolt lock with single-turn latchbolt exclusion and snib. The lock is available with single-sided locking. In the standard version, the lock has a mechanical external visual indicator on the key guide side.



### Properties

- Quick closing of the access panel thanks to automatic deadlocking
- Easy operation with HSL double bit key (single-tour)
- Keyed different, no conversion key required

### Functional description

The latchbolt is locked forwards and backwards via a turn (180° key rotation). The key can be removed when locked and unlocked. When the latchbolt is locked forwards, the access panel can be closed quickly and securely without using a key. The lock locks automatically due to the snib. Changing the locks The locking mechanism can be changed to a different lock when unlocked (deadbolt locked back). This requires a key for the current locking system and a key for the future locking system. The HSL 201 type is designed for the secure locking of inspection flaps in detention room and BGH doors.

### Locations

- Inspection flap

### Technical data

Material	Stainless steel
----------	-----------------

---

## Technical data

Surface	Matt
Faceplate dimension [mm]	200 x 30 x 4
Forend material	Stainless steel
Material deadbolt	Stainless steel
Lock housing material	Stainless steel
Locking mechanism	HSL double bit
Levers	7
Recodability	yes
Weight [kg]	2,1
Lock dimensions [mm]	140 x 22 x 135
latch bolt exclusion mm	15
external visual indicator	mechanical
Closing processes	500.000
Max. lateral transom load capacity [kN]	50
Relative humidity	95% non-condensing
Relative humidity [%]	95% non-condensing