

HSL double bit food hatch lock with latch bolt

Article No.: HSL 201

Cam lock with single-turn cam lock release and snib. The lock is available in single-sided locking. In the standard version, the lock has a mechanical external visual indicator on the key-operated side.



Properties

- Quick closing of the inspection flap thanks to automatic deadlocking
- Easy operation with HSL double bit key (1-turn)
- Keyed to match without a master key

Functional description

The latch bolt is locked and unlocked by turning the key once (180°). The key can be removed when the lock is locked or unlocked. When the latch bolt is locked, the inspection flap can be quickly and securely closed without using a key. The snib locks the lock automatically. Changing the keyed system

The lock mechanism can be changed to a different keyed system when unlocked (deadbolt retracted). This requires a key for the current keyed system and a key for the future keyed system.

The HSL 201 type is designed for the secure locking of inspection flaps in detention room and BGH doors.

Places of use

Inspection flap

Technical specifications



Technical specifications

Material	Stainless steel
Surface	Matt
Face plate dimension [mm]	200 x 30 x 4
Material forend	Stainless steel
- Indicate in a rolleria	
	0
Material deadbolt	Stainless steel
Material lock housing	Stainless steel
Lock mechanism	HSL double bit
Levers	7
Recodability	yes
	<u>·</u>
Weight [kg]	2.1

Look dimensions [mm]	140 x 22 x 135
Lock dimensions [mm]	140 X 22 X 135
bolt lock exclusion mm	15
Closing operations	500,000
Max. lateral bolt load capacity [kN]	50
Relative humidity [%]	95% non-condensing
external visual indicator	mechanically