

HSL double bit food hatch lock with latch bolt, 2-turn

Article No.: HSL 204

Cam lock with double-turn locking mechanism. In the standard version, the lock has a mechanical external visual indicator on the key side for single-sided locking.



Properties

- Easy operation with HSL double bit key (2 turns)
- Locking can be changed without a change key

Functional description

Changing the keyed action

The lock mechanism can be changed to a different keyed action when unlocked (latch bolt retracted). This requires a key for the current keyed action and a key for the future keyed action.

The HSL 204 type is designed for detention room and passage doors. The latch bolt is released by a first turn (180° key rotation) and locked again by a second turn (180° key rotation). The key can be removed in both locked and unlocked condition

Places of use

- Inspection flap

Technical specifications

Material Stainless steel

Surface Matt



Technical specifications

Face plate dimension [mm]	200 x 30 x 4
Material forend	Stainless steel
Material deadbolt	Stainless steel
Material lock housing	Stainless steel
Lock mechanism	HSL double bit
Levers	7
Recodability	yes
Weight [kg]	2.1
Lock dimensions [mm]	140 x 22 x 135
Closing operations	500,000
Max. lateral bolt load capacity [kN]	50
Relative humidity [%]	95% non-condensing
external visual indicator	mechanically
Latch clearance [mm]	15