

HSL double bit retrofit food hatch lock with deadbolt

Article No.: HSL C205

Bolt lock for inspection flaps with single-turn bolt throw (bolt thickness 10 mm). As retrofit for 8.13.0203.0 and 8.13.0204.0



Properties

- 1:1 replacement of previous double-bit locks with HSL C
- Simple operation with HSL double-bit key (1 turn)

Functional description

The HSL double bit key is inserted into the lock.

The deadbolt is locked with the key by turning it once (180°).

The inspection flap can be opened.

The inspection flap is closed.

The deadbolt is pre-locked with the key by turning it once (180°).

The inspection flap is completely locked.

Changing the keyed configuration

The lock can be changed to a different keyed configuration when unlocked (deadbolt locked back).

This requires a key for the current keyed configuration and a key for the future keyed configuration.

Places of use

- Inspection flap

Technical specifications



Technical specifications

Material	Stainless steel
Surface	Matt
Face plate dimension [mm]	225 x 30 x 4
Material forend	Stainless steel
Material deadbolt	Stainless steel
Material lock housing	Stainless steel
Lock mechanism	HSL double bit
Levers	7
Recodability	yes
Weight [kg]	2.5
Lock dimensions [mm]	180 x 22 x 137
Closing operations	500,000
Max. lateral bolt load capacity [kN]	50
Relative humidity [%]	95% non-condensing
bolt throw mm	20