



## HSL double bit retrofit food hatch lock with deadbolt

Article No.: HSL C205

---

Bolt lock for access panels with single-turn bolt throw (bolt thickness 10 mm). As retrofit for 8.13.0203.0 and 8.13.0204.0



### Properties

- 1:1 replacement of previous double-bit locks with HSL C
- Easy to use with HSL double-bit key (single turn)

### Functional description

The HSL double bit key is inserted into the lock. The deadbolt is locked back with the key via a turn (180° turn). The inspection flap can be opened. The inspection flap is closed. The deadbolt is locked forward with the key via a turn (180° turn). The inspection flap is fully locked. Changing the locking mechanism The locking mechanism can be changed to a different locking mechanism in the unlocked state (deadbolt locked back). To do this, a key for the current keyed and a key for the future keyed is required.

### Locations

- Inspection flap

### Technical data

Material	Stainless steel
Surface	Matt
Faceplate dimension [mm]	225 x 30 x 4



Technical data

Forend material	Stainless steel
Material deadbolt	Stainless steel
Lock housing material	Stainless steel
Locking mechanism	HSL double bit
Levers	7
Recodability	yes
Weight [kg]	2,5
Lock dimensions [mm]	180 x 22 x 137
bolt throw mm	20
Closing processes	500.000
Max. lateral transom load capacity [kN]	50
Relative humidity	95% non-condensing
Relative humidity [%]	95% non-condensing