

Flap hinge, flush doors, load capacity up to 80 kg

Article No.: INOFLEX

The INOFLEX stainless steel flap hinge series comprises two versions for flush door elements. Thanks to their smart design, the hinges can be installed even in the narrowest of spaces. While INOFLEX1 is the lift-off version, INOFLEX2 is the solution with double bearing



Properties

- For flush doors
- Load capacity with two hinges up to 80 kg
- Stainless steel investment casting, brushed and blasted
- 2D adjustability
- Available in rising or non-rising
- Can be used on the right-hand or left-hand side
- Lift-off version (non-lift-off – INOFLEX2)
- Covering caps with safety catch
- Quick and easy assembly
- For indoor and outdoor use
- Opening angle max. 270°

Functional description

The INOFLEX1 stainless steel flap hinge combines modern design with the highest quality and practical functionality. With rising and non-rising versions, we can find the optimal solution for individual requirements for flush doors up to 80 kg. Intuitive and simple assembly can be completed in no time at all.

Places of use

- Cold room manufacturer
- Refrigerated vehicles
- Cooling fitting trade
- Metal/door construction
- Refrigerator door manufacturer

Technical specifications

| | |
|--------------------|----------------------------------------|
| Offset [mm] | 0 |
| Material | Stainless steel |
| Surface | Grinded and blasted |
| Door version | Right-hand version / Left-hand version |
| Adjustability | 2D |
| Opening angle | 270 |
| Door type | Hinged doors |
| Slope | Yes / No |
| Safety | Yes |
| Load capacity [kg] | up to 100 |

