

Flap hinge, flush doors, load capacity up to 80 kg

Article No.: INOFLEX

The INOFLEX 2 stainless steel flap hinge series includes 2 versions for flush door elements. Thanks to their smart design, the hinges fit into even the narrowest installation situations. While INOFLEX1 is the lift-off version, INOFLEX2 is a convincing solution with double bearing



Properties

- For flush doors
- Load capacity of up to 80 kg with two hinges
- Stainless steel investment casting, brushed and blasted
- 2D adjustability
- Available in rising or non-rising
- Can be used on the right or left-hand side
- Lift-off version (not lift-off – INOFLEX2)
- Secured covering caps
- Quick and easy assembly
- For indoor and outdoor use
- Opening angle of max. 270°

Functional description

The INOFLEX1 stainless steel flap hinge combines modern design with the highest quality and practical functionality. With the rising and non rising versions, we have the optimum solution for individual requirements for flush doors weighing up to 80 kg. The intuitive and simple assembly can be completed in no time at all.

Places of use

- Cold room manufacturer
- Refrigerated vehicles
- Refrigerated hardware trade
- Metal/door construction
- Refrigerated door manufacturer

Technical specifications

Load capacity [kg]	up to 100
Offset [mm]	0
Material	Stainless steel
Surface	Grinded and blasted
Door version	Right-hand version / left-hand version
Adjustability	2D
Opening angle	270°
Door type	Hinged door
Slope	Yes / No
Load capacity	up to 100
Offset	0
Safety	Yes

