

## MAXIFLEX Heavy-duty sling, load capacity up to 240 kg

Article No.: MAXIFLEX2.FLP

---

The heavy-duty hinges in the MAXIFLEX series meet the highest demands and are therefore ideal for use in medium-duty or heavy-duty flush doors or overlapping doors in insulation technology



### Properties

- Load capacity with two hinges up to 240 kg
- Modern design for high-quality door design
- Stainless steel investment casting, grinded and blasted
- Can be used for right-hand and left-hand doors
- Different colour combinations
- Adjustable in two shafts, rising / non-rising
- Maximum opening angle of 180°
- For doors with 0 and 32 mm offset
- Reliable removal protection
- Modular design: single components can be replaced
- Stainless steel riser for use in extreme environments

### Functional description

The MAXIFLEX flap hinge made of AISI304 stainless steel impresses with a load capacity of up to 240 kg. The two-tone look with black caps adds an elegant highlight and enhances any door. High-quality materials and double hinge pin bearings guarantee smooth operation. The flap hinge offers 2D adjustability, enabling precise adjustment even in difficult installation locations.

### Places of use

- Cold room manufacturer
- Refrigerated vehicles
- Cooling fitting trade
- Metal/door construction
- Refrigerator door manufacturer

### Technical specifications

Load capacity [kg]	up to 240
Offset [mm]	from 60
Material	Stainless steel
Surface	Grinded and blasted
Door version	Right-hand version / Left-hand version
Adjustability	2D
Opening angle	180
Door type	Hinged doors
Accessories	Shims
Slope	Yes / No
Load capacity	up to 240
Offset	from 60
Safety	No

**SECURITY  
MADE IN GERMANY  
SINCE 1883**



**SECURITY  
MADE IN GERMANY  
SINCE 1883**



