



PYLOCX control module 48V (external power supply required)

Article No.: PL2012

PYLOCX® control module designed for 48V power supply.

Properties

- PYLOCX control module 48V
- Designed for operation when energised
- Opening by one-time code or fixed PIN
- Readable opening protocol up to 10,000 entries
- VdS certified
- IP52
- Temperature range -20°C - 50°C

Functional description

After entering the code, the PYKEY® is placed on the corresponding contact point of the device. The code is transmitted and the device is supplied with power for opening if necessary. When energised, automatic keying is possible via the door-bolt contact.

Technical data

Material	Composite materials
Surface	Rough
Colour	Black
Dimensions LxWxH	99.5 x 89 x 33mm

Technical data

Standards	VdS 2.344:2.014-07 , VdS 2.369:2.022-09 , EN 1.300:2.013-11
-----------	---

Fixing type	Screw-on
-------------	----------

IP-Rating	IP52
-----------	------

Temperature range	-25°C - +50°C
-------------------	---------------

Locking function	Electronic
------------------	------------

Locking set	PYKEY
-------------	-------

Locking type	Manual keyed, automatic keyed
--------------	-------------------------------

Utilisation	Control of connected locks or other devices
-------------	---

Safety class	VdS Class 2 EN 1.300 Class B
--------------	------------------------------

Operating voltage	48V DC
-------------------	--------

Dimensions [mm]	99.5 x 89 x 33
-----------------	----------------