

## PYLOCX control module 12V - VdS class 2

Article No.: PL2014

---

PYLOCX® control module designed for 12V power supply or unpowered continuous operation. Encrypted transmission to the motorised lock via VLink. VdS class 2.



### Properties

- PYLOCX control module 12V
- Designed for power-free operation
- Opening by one-time code or fixed PIN
- Readable opening protocol up to 10,000 entries
- VdS-certified, class 2
- IP52
- Temperature range -20°C - 50°C
- Encrypted transmission via Vlink

### Functional description

After entering the code, the PYKEY® is placed on the corresponding contact point of the device. The code is transmitted and the device is supplied with power for opening if necessary. When energised, automatic keying is possible via the door-bolt contact.

### Technical data

Material Composite materials

---

Surface Rough

---

Colour Black

---



## Technical data

Dimensions LxWxH	99.5 x 89 x 33mm
Standards	VdS 2.344:2.014-07 , VdS 2.369:2.022-09 , EN 1.300:2.013-11
Fixing type	Screw-on
IP-Rating	IP52
Feature	Continuous unpowered operation possible, encrypted transmission via VLink
Temperature range	-25°C - +50°C
Locking function	Electronic
Locking set	PYKEY
Locking type	Manual keyed, automatic keyed
Utilisation	Control of connected locks or other devices
Safety class	VdS Class 2 EN 1.300 Class B
Operating voltage	12V DC
Dimensions [mm]	99.5 x 89 x 33