Data sheet

SECURITY
MADE IN GERMANY
SINCE 1883

PYLOCX motor lock 12V

Article No.: PL2044

The PL2044 motor lock can be opened and closed from any PYLOCX control module. Monitoring of the bolt status is also possible.



Properties

- Compatible with all PYLOCX control modules
- Opening possible in permanently de-energised operation

Functional description

After PYKEY and the control module have signalled an opening, the PL2044 motor lock opens or closes the motor bolt. In de-energised operation, the PYKEY supplies the energy for opening and keyed locking.

Technical specifications

Material	Steel
Surface	Zinc-plated
Colour	Silver
Standards	VdS 2.344:2.014-07 / VdS 2.369:2.022-09 / EN 1.300:2.013-11
Fixing type	Screw-on
IP-Rating	IP30
Temperature range	+5°C to +40°C

SECURITY
MADE IN GERMANY
SINCE 1883

Technical specifications

Locking function	Electronic
Locking set	PYKEY
Lock type	Manual keyed, automatic locking
Stroke [mm]	12
Use	Electronic motor lock for control modules
Security class	For systems with VdS Class 2 and 3
Dimensions LxWxH	With deadbolt: 100 x 60.7 x 34 mm
Weight [kg]	480 g



SECURITY
MADE IN GERMANY
SINCE 1883





Steinbach & Vollmann GmbH | Parkstraße 11 42579 Heiligenhaus | +492056140 | info@stuv.de | www.stuv.de

SECURITY
MADE IN GERMANY
SINCE 1883



Steinbach & Vollmann GmbH | Parkstraße 11 42579 Heiligenhaus | +492056140 | info@stuv.de | www.stuv.de