

PYLOCX locking device (VdS)

Article No.: PL3015-SB-V44

Locking device for connecting PYLOCX systems to EMA/EMZ systems. Available with or without surface protection.



Properties

- Compatible with PYLOCX control modules
- Connection to EMA/EMZ systems Class C
- Optional surface protection
- Designed for live operation

Functional description

After entering the code, the PYKEY is placed on the corresponding contact point on the device. The code is transmitted in encrypted form and the device opens. When powered, automatic keying is possible via a door bolt contact. EMA and EMZ systems can thus be integrated into a PYLOCX system in accordance with VdS.

Technical specifications

Material	Aluminium
Surface	Rough
Colour	Black
Standards	VdS 2.344:2.014-07, VdS 2.110:2.017-09, VdS 2.203:2.001-03, VdS 2.119:2.003-12, VdS
Fixing type	2.271:2.007-12 Screw-on

Technical specifications

IP-Rating	IP32
Feature	With or without surface protection
Temperature range	-25°C to +50°C
Locking function	Electronic
Locking set	PYKEY
Lock type	Manual keyed, automatic locking
Use	Locking device for EMA, EMZ
Security class	For EMA, EMZ Class C
Operating voltage	12V DC via connected EMA, EMZ
Dimensions LxWxH	120 x 120 x 30 mm

