

## PYLOCX® cylinder for key depot PL401X

Article No.: PL4012

The standard cylinder for the PL4011-SB tubular safe slide-in module, available in 185mm length (with or without reed contact) or 255mm length.



### Properties

- Compatible with PL401X locking mechanism
- PL4012: Inner L 95mm Ø 61.6mm / Outer L 185mm Ø 69.5mm
- PL4012-A: Inner L 165mm Ø 61.6mm / Outer L 255mm Ø 69.5mm
- PL4012-R: Inside L 95mm Ø 61.6mm / Outside L 185mm Ø 69.5mm
- Opening status monitored by reed contact (PL4012-R)
- Flush-mounted assembly through core drilling
- Installation in free-standing columns and hollow walls possible
- Temperature range -35°C - + 60°C
- Suitable for indoor and outdoor use with IP63
- VdS-certified

### Functional description

After VdS-compliant assembly of this cylinder, various keys or valuables can be securely stored in conjunction with the PYLOCX® PL4011-SB slide-in module.

### Technical data

Material	Aluminium
Surface	Hard anodised



Technical data

Colour	Grey
Dimensions LxWxH	Inside L 95/165mm Ø 61.6mm / Outside L 185/255mm Ø 69.5mm
Standards	VdS 2.105:2.013-10 / VdS 2.110:2.017-09 / VdS 2.344:2.014-07 / DIN 14.675 Annex
Fixing type	C:2.003-11 Core drilling
IP-Rating	IP63
Feature	Optional reed contact, various cylinder lengths available
Temperature range	-35°C - +60°C
Utilisation	Cylinder for PL4.011-SB tube safe
Safety class	VdS class SD1 Environmental class IV
Dimensions [mm]	Inside L= 95/165 x Ø 61.6 / Outside L= 185/255 x Ø 69.5

| SECURITY  
| MADE IN GERMANY  
| SINCE 1883



**SECURITY  
MADE IN GERMANY  
SINCE 1883**

