

## PYLOCX® cylinder for key depot PL402X

Article No.: PL4012-B

---

The standard cylinder for the PL4021-SB tube safe slide-in module.



### Properties

- Compatible with PL402X locking insert
- Inner length 196mm Ø 64.6mm
- Outer length 275mm Ø 69.5mm
- Flush-mounted assembly through core drilling
- Installation in free-standing columns and hollow walls possible
- Temperature range -35°C - + 60°C
- Suitable for indoor and outdoor use with IP63
- VdS-certified

### Functional description

After VdS-compliant assembly of this cylinder, various keys or valuables can be securely stored in conjunction with the PYLOCX® PL4021-SB slide-in module.

### Technical data

Material	Aluminium
Surface	Hard anodised
Colour	Grey
Dimensions LxWxH	Inside L 196mm Ø 64.6mm / Outside L 275mm Ø 69.5mm



Technical data

Standards	VdS 2.105:2.013-10 / VdS 2.110:2.017-09 / VdS 2.344:2.014-07 / DIN 14.675 Annex
Fixing type	C:2.003-11 Core drilling
IP-Rating	IP63
Temperature range	-35°C - +60°C
Utilisation	Cylinder for PL4.021-SB tube safe
Safety class	VdS class SD1 Environmental class IV
Dimensions [mm]	Inside L= 196 x Ø 64.6 / Outside L= 275 x Ø 69.5