Data sheet

SECURITY
MADE IN GERMANY
SINCE 1883

PYLOCX Retrofit lock insert for ASSA ABLOY key safe/key deposit box

Article No.: PL403X

The PYLOCX retrofit lock cylinder is specially designed for the ASSA ABLOY key safe and enables easy and secure retrofitting of existing locking systems without the need for structural changes. This allows modern locking technology to be easily integrated into existing infrastructures.



Properties

- PYLOCX key safe in alternative version
- Dimensions of lock insert: Ø 35 - 67 mm
- Compatible with ASSA ABLOY wall safe tubes
- Non-powered operation
- Opening with one-time code or fixed PIN
- Readable opening log with up to 10,000 entries
- Suitable for indoor and outdoor use

Functional description

After entering the code, the PYKEY is placed on the contact point of the device. The code is transmitted and the device is supplied with power to open. The lock insert can be pulled out manually using the magnetic force of the PYKEY. When the lock insert is pushed back in, it locks automatically.


Technical specifications

Temperature range	-35°C to +60°C
Locking function	Electronic

SECURITY
MADE IN GERMANY
SINCE 1883

Technical specifications

Locking set	PYKEY
Lock type	Automatic deadlocking
Use	PYLOCX lock insert for ABLOY key deposit - inner diameter 33 mm
Dimensions LxWxH	Inner diameter 33 mm








PYKEY