

**PYLOCX lock insert for KRUSE key deposit - inner diameter 67 mm**

Article No.: PL406X

PYLOCX lock insert for KRUSE key deposit - inner diameter 67 mm

**Properties**

- PYLOCX key deposit box in alternative version
- Dimensions of lock insert: Ø 67 mm
- Compatible with KRUSE wall safe tubes
- Non-electric operation
- Opening with one-time code or fixed PIN
- Readable opening log with up to 10,000 entries
- Suitable for indoor and outdoor use



**Functional description**

After entering the code, the PYKEY is placed on the contact point of the device. The code is transmitted and the device is supplied with power to open. The lock insert can be pulled out manually using the magnetic force of the PYKEY. When the lock insert is pushed back in, it locks automatically.

**Technical specifications**

Material	Stainless steel (AISI 316)
Colour	Silver
Dimensions LxWxH	Inner diameter 67mm
Mounting hole	67 mm

## Technical specifications

Housing diameter	66 mm
Length of housing	45 mm
Insert	Via PYKEY
Assembly	RETROFIT version for Kruse pipe safes
IP-Rating	IP65
Temperature range	-35°C to +60°C
Locking function	Electronic
Locking type	Automatic deadlocking
Locking set	PYKEY
Lock type	Automatic deadlocking
Lock dimensions [mm]	66
Relative humidity	80%
Use	PYLOCX lock insert for KRUSE key deposit - inner diameter 67 mm
Charging technology	Via PYKEY
Dimensions [mm]	Inner diameter 67