

PYLOCX® locking mechanism for KRUSE key depot – inner diameter 67mm

Article No.: PL406X

PYLOCX® locking insert for KRUSE key depot - inner diameter 67mm



Properties

- PYLOCX key depot in alternative version
- Dimensions of locking insert: Ø 67mm
- Compatible with KRUSE wall safe tubes
- No-electricity operation
- Opening by one-time code or fixed PIN
- Readable opening protocol up to 10,000 entries
- Suitable for indoor and outdoor use

Functional description

After entering the code, the PYKEY® is placed on the contact point of the device. The code is transmitted and the device is supplied with power for opening. The locking insert can be pulled out manually using the magnetic force of the PYKEY®. When the locking insert is pushed back in, it locks automatically.

Technical data

Material	Edelstahl (AISI 316)
Colour	Silbern
Dimensions LxWxH	Inner diameter 67mm
Installation opening	67mm



Technical data

Case diameter	66mm
Length of housing	45mm
Insert	Via PYKEY
Assembly	RETROFIT-Variante für Kruse-Rohrtresore
IP-Rating	IP65
Temperature range	-35°C - +60°C
Locking function	Electronic
Locking type	Selbstverriegelnd
Locking set	PYKEY
Locking type	Automatic deadlocking
Lock dimensions [mm]	66
Relative humidity	80%
Utilisation	PYLOCX® locking insert for KRUSE key depot - inner diameter 67mm
Charging technology	Via PYKEY
Dimensions [mm]	Inside Ø 67