

PYLOCX cylinder for key deposit PL401X

Article No.: PL4100.D61.L185

The standard cylinder for the PL4011-SB tube safe insert module, available in 185 mm length (with or without reed contact) or 255 mm length.



Properties

- Compatible with PL401X lock insert
- PL4012: Internal L 95 mm Ø 61.6 mm / External L 185 mm Ø 69.5 mm
- PL4012-A: Internal L 165 mm Ø 61.6 mm / External L 255 mm Ø 69.5 mm
- PL4012-R: Inside L 95 mm Ø 61.6 mm / Outside L 185 mm Ø 69.5 mm
- Control of opening status via reed contact (PL4012-R)
- Flush-mounted assembly via core drilling
- Installation in free-standing columns and hollow walls possible
- Temperature range -35°C to + 60°C
- Suitable for indoor and outdoor use thanks to IP63
- VdS certified

Functional description

After assembly of this cylinder in accordance with VdS, various keys or valuables can be securely stored in conjunction with the PYLOCX PL4011-SB insert module.

Technical specifications

Material	Aluminium
Surface	Hard anodised

Technical specifications

Colour	Grey
Standards	VdS 2.105:2.013-10 / VdS 2.110:2.017-09 / VdS 2.344:2.014-07 / DIN 14.675 Annex
Fixing type	C:2.003-11 Core drilling
IP-Rating	IP63
Feature	Optional reed contact, various cylinder lengths available
Temperature range	-35°C to +60°C
Use	Cylinder for tube safe PL4.011-SB
Security class	VdS Class SD1 Environmental Class IV
Dimensions LxWxH	Inner L 95/165 mm Ø 61.6 mm / Outer L 185/255 mm Ø 69.5 mm



**SECURITY
MADE IN GERMANY
SINCE 1883**



**SECURITY
MADE IN GERMANY
SINCE 1883**

