

PYLOCX cylinder for key deposit PL402X

Article No.: PL4100.D61.L275

The standard cylinder for the PL4021-SB tube safe insert module.

Properties

- Compatible with PL402X lock insert
- Internal length 196 mm, Ø 64.6 mm
- External length 275 mm, Ø 69.5 mm
- Flush mounting via core drilling
- Installation in free-standing columns and hollow walls possible
- Temperature range -35°C to + 60°C
- Suitable for indoor and outdoor use thanks to IP63
- VdS certified



Functional description

After assembly of this cylinder in accordance with VdS, various keys or valuables can be securely stored in conjunction with the PYLOCX PL4021-SB insert module.

Technical specifications

Material	Aluminium
Surface	Hard anodised
Colour	Grey
Standards	VdS 2.105:2.013-10 / VdS 2.110:2.017-09 / VdS 2.344:2.014-07 / DIN 14.675 Annex C:2.003-11

Technical specifications

Fixing type	Core drilling
IP-Rating	IP63
Temperature range	-35°C to +60°C
Use	Cylinder for tube safe PL4.021-SB
Security class	VdS Class SD1 Environmental Class IV
Dimensions LxWxH	Inner L 196 mm Ø 64.6 mm / Outer L 275 mm Ø 69.5 mm