

## PYLOCX Comfort Europrofil knob cylinder

Article No.: PL60XX

The PL6021 Comfort series knob cylinders are available in sizes from 25mm inside / 30mm outside to 55mm inside / 65mm outside (5mm increments). All models are available with or without recess and can be installed in mortise locks with EURO profile cylinder insert.



### Properties

- 25mm inside / 30mm outside up to 55mm inside / 65mm outside
- Optionally with recess
- Cylinder lock with Euro profile
- Temperature range -30°C - + 60°C
- No-power operation
- Opening by one-time code or fixed PIN
- Readable opening protocol up to 10,000 entries
- VdS-certified
- Suitable for indoor and outdoor use with IP65

### Functional description

After entering the code, the PYKEY® is placed on the contact point of the device. The code is transmitted and the device is supplied with power for opening. After pulling out the knob, it can be turned to open. When closed, the outer knob rotates freely.

### Technical data

Door thickness [mm]

Knob side (inside): 25-55mm, contact point side (outside): 35-65mm

## Technical data

Material	Brass
Surface	Nickel-plated
Colour	Silver
Standards	VdS 2.344:2.014-07 , VdS 2.156-2:2.013-06 , VdS 2.386:2.012-07 , DIN EN
Fixing type	15.684:2.013-02 For mortise locks with Euro profile cylinder insert
IP-Rating	IP65
Feature	With or without return
Temperature range	-30°C - + 60°C
Door thickness	Knob side (inside): 25-55mm, contact point side (outside): 35-65mm
Locking function	Electronic
Locking set	PYKEY
Locking type	Manual keyed
Utilisation	Euro profile cylinder
Safety class	VdS KL. BZ***

**SECURITY  
MADE IN GERMANY  
SINCE 1883**

