

# PYLOCX Compact Euro profile double cylinder

Article No.: PL62XX

The PYLOCX Compact Euro profile double cylinder, available in sizes from 30 mm inside / 30 mm outside to 60 mm inside / 60 mm outside (in 5 mm increments). Optionally available with a 7.2 mm extension.

### Functional description

After entering the code, the PYKEY is placed on the contact point of the device. The code is transmitted and the device is supplied with power to open. After pulling out the knob, it can be turned to open. When closed, the outer knob turns freely.

# Technical specifications

| Material          | Brass                              |                                 |
|-------------------|------------------------------------|---------------------------------|
|                   |                                    |                                 |
| Surface           | Nickel-plated                      |                                 |
| Colour            | Silver                             |                                 |
| Fixing type       | For mortise locks with Swiss round | d profile cylinder plug-in unit |
| IP-Rating         | IP68                               |                                 |
| Feature           | Optional with 7.2 mm extension     |                                 |
| Temperature range | -40°C to +60°C                     |                                 |
| Locking function  | Electronic                         |                                 |
| Locking set       | PYKEY                              |                                 |
| Lock type         | Manual keyed                       |                                 |



# Technical specifications

| Use                 | Euro profile double cylinder       |  |
|---------------------|------------------------------------|--|
|                     |                                    |  |
| Door thickness [mm] | Contact point side (inside): 30-60 | mm, contact point side (outside): 30-60 mm |