
Data sheet

SECURITY
MADE IN GERMANY
SINCE 1883

PYLOCX Compact Euro profile half cylinder

Article No.: PL63XX

The PYLOCX Compact Europrofile half cylinder, available in sizes 0 inside / 30 mm outside to 0 inside / 60 mm outside (in 5 mm increments). Optionally available with 7.2 mm extension, as well as a spring-loaded version for swing handles.



Properties

- 0 mm inside / 30 mm outside to 0 mm inside / 60 mm outside
- Optionally with extension or spring
- Cylinder lock with Euro profile
- Temperature range -40°C - + 60°C
- De-energised operation
- Opening with one-time code or fixed PIN
- Readable opening log with up to 10,000 entries
- VdS certified
- Suitable for indoor and outdoor use thanks to IP68

Functional description

After entering the code, the PYKEY is placed on the contact point of the device. The code is transmitted and the device is supplied with power to open. After pulling out the knob, it can be turned to open. When closed, the outer knob turns freely.

Places of use

- Der Halbzylinder eignet sich für Türen mit Euro-Profilzylinder in technischen oder sicherheitsrelevanten Bereichen wie Infrastruktur-, Technik- oder Versorgungsanlagen. Dank Möglichkeit des Einmalcode-Zugang und Protokollfunktion eignet sich das System besonders für Anwendungen mit wechselnden Zutrittsberechtigungen oder erhöhten Sicherheitsanforderungen..

Technical specifications

SECURITY
MADE IN GERMANY
SINCE 1883

Technical specifications

Material	Brass and stainless steel
Surface	Nickel-plated
Colour	Silver
Fixing type	For mortise locks with Euro profile cylinder plug-in unit
IP-Rating	IP68
Feature	Optional 7.2 mm extension for doors with security hardware; optional spring-loaded version for swinghandles, for example
Temperature range	-40°C to +60°C
Locking function	Electronic
Locking set	PYKEY
Lock type	Manual keyed
Door type	Access doors and service doors
Use	Euro profile half cylinder
Door thickness [mm]	Knob side (inside): 0, contact point side (outside): 30–60 mm

SECURITY
MADE IN GERMANY
SINCE 1883



Steinbach & Vollmann GmbH | Parkstraße 11 42579 Heiligenhaus | +492056140 | info@stuv.de | www.stuv.de