


PYLOCX Compact Euro profile half cylinder

Article No.: PL63XX

The PYLOCX Compact Europrofile half cylinder, available in sizes 0 inside / 30 mm outside to 0 inside / 60 mm outside (in 5 mm increments). Optionally available with 7.2 mm extension, as well as a spring-loaded version for swing handles.



Properties

- 0 mm inside / 30 mm outside to 0 mm inside / 60 mm outside
- Optionally with extension or spring
- Cylinder lock with Euro profile
- Temperature range -40°C - + 60°C
- De-energised operation
- Opening with one-time code or fixed PIN
- Readable opening log with up to 10,000 entries
- VdS certified
- Suitable for indoor and outdoor use thanks to IP68

Functional description

After entering the code, the PYKEY is placed on the contact point of the device. The code is transmitted and the device is supplied with power to open. After pulling out the knob, it can be turned to open. When closed, the outer knob turns freely.

Technical specifications

Material

Brass

Technical specifications

Surface	Nickel-plated
Colour	Silver
Fixing type	For mortise locks with Euro profile cylinder plug-in unit
IP-Rating	IP68
Feature	Optional with 7.2 mm extension, optional spring-loaded version for swinghandle
Temperature range	-40°C to +60°C
Locking function	Electronic
Locking set	PYKEY
Lock type	Manual keyed
Use	Euro profile half cylinder
Door thickness [mm]	Knob side (inside): 0, contact point side (outside): 30–60 mm

**SECURITY
MADE IN GERMANY
SINCE 1883**

