


## PYLOCX Compact Europrofil Half Cylinder

Article No.: PL63XX

The PYLOCX® Compact Euro profile half cylinder, available in sizes 0 inside / 30mm outside to 0 inside / 60mm outside (in 5mm increments). Optionally available with 7.2mm extension, as well as spring-loaded version for swivelling lever.



### Properties

- 0mm inside / 30mm outside up to 0mm inside / 60mm outside optionally with extension or spring-loaded Cylinder lock with Euro profile Temperature range -40°C - + 60°C Currentless operation Opening by one-time code or fixed PIN Readable opening protocol up to 10,000 entries VdS-certified Suitable for indoor and outdoor use due to IP68

### Functional description

After entering the code, the PYKEY® is placed on the contact point of the device. The code is transmitted and the device is supplied with power for opening. After pulling out the knob, it can be turned to open. When closed, the outer knob rotates freely.

### Technical data

Door thickness [mm]	Knob side (inside): 0 , contact point side (outside): 30-60mm
Material	Brass
Surface	Nickel plated
Colour	Silver
Fixing type	For mortise locks with Euro profile cylinder insert
IP-Rating	IP68
Feature	Optional with 7.2 mm extension, optional spring-loaded version for swivelling lever

Technical data

Temperature range	-40°C - +60°C
Door thickness	Knob side (inside): 0 , contact point side (outside): 30-60mm
Locking function	Electronic
Locking set	PYKEY
Locking type	Manual keyed
Utilisation	Euro profile half cylinder
WebGL	<a href="https://api.sts.sch-server.de/sync/renderings/PYLOCX_Sicherheits">https://api.sts.sch-server.de/sync/renderings/PYLOCX Sicherheits</a> Profilzylinder/Stuv_Zylinderschloss_KurzKnauf_01.glb

