



PYLOCX® electronic door lock

Article No.: PL70XX

Battery-free electronic security fitting, optionally with/without mechanical profile cylinder emergency locking. Suitable for 7/8/9mm Nut, 70/72/85/88/92mm spacing. Suitable for interior and exterior applications as well as fire doors.



Properties

- Universally applicable security fitting
- Solid stainless steel
- Open using a one-time code or PIN
- Suitable for indoor and outdoor use, as well as for fire doors
- Mechanical profile cylinder emergency locking possible
- Various profiles available

Functional description

After entering the code, the PYKEY® is placed on the contact point of the device. The code is transmitted and the device is supplied with power for opening. The door can now be opened using the unlocked door handle.

Technical data

| | |
|------------------|---|
| Material | Stainless steel |
| Colour | Silver |
| Dimensions LxWxH | Profiles: Without, 70/72/85/88/92mm, Nut: 7/8/9mm |
| Standards | EI60, EN16.867 |

Technical data

| | |
|------------------|---|
| IP-Rating | IP68 |
| Locking function | Electronic |
| Locking set | PYKEY |
| Locking type | Automatic deadlocking |
| Utilisation | Electronic door fitting |
| Dimensions [mm] | Profiles: Without, 70/72/85/88/92, Nut: 7/8/9 |



| SECURITY
MADE IN GERMANY
SINCE 1883

