

PYLOCX® Swinghandle Lock

Article No.: PL71XX

Swivelling lever with integrated PYLOCX® security half cylinder.

Properties

- Electronic cylinder with solid stainless steel knob
- Swivel handle made of weatherproof zinc die-cast
- Burglary protection: resistance class 2
- Suitable for all hole sizes
- For indoor and outdoor use (IP68)
- Existing swivel handles can be replaced (retrofit)

Functional description

The power and data transfer for releasing the swivelling lever is carried out using the PYKEYS. After authentication, the electronic half cylinder is released and the swivelling lever can be opened by turning the convenient operating knob. A 45° movement inserts the linkage behind the swivelling lever and you have the option of locking or unlocking.

Technical data

Material	Zamak 5
Colour	Black
Fixing type	Screw-on
IP-Rating	IP65





Technical data

Temperature range	-40°C - +60°C
Locking function	Electronic
Locking set	PYKEY
Locking type	Automatic deadlocking
Utilisation	Power boxes, distribution boxes, HVAC, telecommunications, transport
WebGL	https://api.sts.sch-server.de/sync/renderings/PYLOCX
Dimensions [mm]	Schwenkgriff/Stuv_Schwenkschloss_01.glb 40 x 163 x 66
Diffictionolis [fillift]	40 X 100 X 00



