



PYLOCX padlock

Article No.: PL73XX

Electronic high-security padlock made of solid stainless steel with integrated PYLOCX® locking system. Vandal-resistant stainless steel knob and very high corrosion resistance. Selectable shackle heights 25mm to 75mm, shackle thickness 8mm or 11mm, shackle material stainless steel or molybdenum.



Properties

- Universal padlock
- Solid stainless steel
- Shackle material stainless steel or molybdenum
- Shackle heights 25mm, 50mm, 75mm
- Shackle thickness 8mm, 11mm
- Seawater resistant
- Opening by single-use code or PIN
- High security version with hidden shackle available

Functional description

After entering the code, the PYKEY® is placed on the contact point of the device. The code is transmitted and the device is supplied with power for opening. The padlock shackle can now be opened.

Technical data

Material	Stainless steel
Surface	Brushed

Technical data

Colour	Silver
Dimensions LxWxH	Bow diameter 8mm / 11mm, bow height 25mm / 50mm / 75mm
Standards	EN16.864
IP-Rating	IP68
Temperature range	-40°C - +60°C
Locking function	Electronic
Locking set	PYKEY
Locking type	Manual keyed
Utilisation	Electronic padlock
Dimensions [mm]	Bracket diameter 8 / 11, bracket height 25 / 50 / 75



**SECURITY
MADE IN GERMANY
SINCE 1883**

