



PYLOCX padlock

Article No.: PL73XX

High-security electronic padlock made of solid stainless steel with integrated PYLOCX locking system. Vandal-proof stainless steel knob and very high corrosion resistance. Selectable shackle heights from 25 mm to 75 mm, shackle thickness 8 mm or 11 mm, shackle material stainless steel or molybdenum.



Properties

- Universally applicable padlock
- Solid stainless steel
- Shackle material stainless steel or molybdenum
- Shackle heights 25 mm, 50 mm, 75 mm
- Shackle thickness 8 mm, 11 mm
- Seawater resistant
- Opening via one-time code or PIN
- High-security version with concealed shackle available

Functional description

After entering the code, the PYKEY is placed on the contact point of the device. The code is transmitted and the device is supplied with power for opening. The padlock shackle can now be opened.

Technical specifications

Material	Stainless steel
Surface	Brushed

Technical specifications

Colour	Silver
Standards	EN16.864
IP-Rating	IP68
Temperature range	-40°C to +60°C
Locking function	Electronic
Locking set	PYKEY
Lock type	Manual keyed
Use	Electronic padlock
Dimensions LxWxH	Hanger diameter 8 mm / 11 mm, hanger height 25 mm / 50 mm / 75 mm



**SECURITY
MADE IN GERMANY
SINCE 1883**

