

## PYLOCX manhole cover lock

Article No.: PL74XX

---

Self-locking locking insert for manhole covers from all common manufacturers, dimensionally identical replacement for cylinder locking inserts. Suitable for manhole covers up to RC3 according to DIN EN 1627 in class D400. Suitable for use in Ex zone 1. Various versions with diameters 35/40 mm, with/without flange.



### Properties

- Universally applicable lock insert
- Opening via one-time code or PIN
- Suitable for manhole covers up to RC3 according to DIN EN 1627 in class D400
- Suitable for use in Ex zone 1
- Various sizes available

### Functional description

After entering the code, the PYKEY is placed on the contact point of the device. The code is transmitted and the device is supplied with power to open. The lock insert can be pulled out manually. When the lock insert is pushed back in, it locks automatically.

### Technical specifications

Material	Brass
Fixing type	Plug-in unit for existing shaft covers
IP-Rating	IP65
Temperature range	-40°C to +60°C

## Technical specifications

Locking function	Electronic
Locking set	PYKEY
Lock type	Automatic deadlocking
Use	Dimensionally identical replacement for cylinder lock inserts
Dimensions LxWxH	Ø33/35/40/46 mm



**SECURITY  
MADE IN GERMANY  
SINCE 1883**

