

PYLOCX manhole cover lock

Article No.: PL74XX

Self-locking locking insert for manhole covers from all common manufacturers, dimensionally identical replacement for cylinder locking inserts. Suitable for manhole covers up to RC3 in accordance with DIN EN 1627 in class D400. Suitable for insert part in Ex zone 1. Different variants with diameter 35/40 mm, with/without flange.



Properties

- Universally applicable insert part
- Opening by means of one-time code or PIN
- Suitable for manhole covers up to RC3 according to DIN EN 1627 in class D400
- Suitable for use in Ex zone 1
- Different sizes available

Functional description

After entering the code, the PYKEY® is placed on the contact point of the device. The code is transmitted and the device is supplied with power for opening. The locking insert can be pulled out manually. When the locking insert is pushed back in, it locks automatically.

Technical data

Material	Brass
Dimensions LxWxH	Ø33/35/40/46mm
Fixing type	Plug-in unit in existing manhole cover

Technical data

IP-Rating	IP65
Temperature range	-40°C - +60°C
Locking function	Electronic
Locking set	PYKEY
Locking type	Automatic deadlocking
Utilisation	Dimensionally identical replacement for cylinder lock inserts
WebGL	https://api.sts.sch-server.de/sync/renderings/PYLOCX
Dimensions [mm]	Brunnenschloss/Stuv_Schachtdeckelschloss_01 (1).glb Ø 33/35/40/46



**SECURITY
MADE IN GERMANY
SINCE 1883**

