

SL profile cylinder bolt lock

Article No.: SL 101

Bolt lock with single-turn bolt throw. In the standard version, the lock has a mechanical external visual indicator on the fitting side.



Properties

- Simple operation, pre-equipped for Euro profile cylinders
- The lock can be locked on one or both sides by using profile half cylinders or double profile cylinders

Functional description

Personnel:

The profile cylinder key is inserted into the profile cylinder.

The deadbolt is locked with the key by turning it once (360° rotation).

The door can be opened.

The door is closed.

The deadbolt is pre-locked with the key by turning it once (360° rotation).

The door is completely locked.

Places of use

- Passage door
- Technical room
- Sanitary room
- Patient door, psychiatric ward

Technical specifications

Technical specifications

Material	Stainless steel
Surface	Matt
Face plate dimension [mm]	280 x 30 x 4
Material forend	Stainless steel
Material deadbolt	Stainless steel
Material lock housing	Stainless steel
Lock mechanism	prepared for profile half cylinders
Recodability	no
Weight [kg]	2.0
Lock dimensions [mm]	200 x 22 x 220
external visual indicator	mechanically
Closing operations	500,000
Max. lateral bolt load capacity [kN]	50
Relative humidity [%]	95% non-condensing
bolt throw mm	20