

SL profile cylinder locking bolt lock

Article No.: SL 101

Bolt lock with single-turn bolt throw. In the standard version, the lock has a mechanical external visual indicator on the fitting side.



Properties

- Easy to use, prepared for Euro profile cylinder
- By using profile half or profile double cylinders, the lock can be closed on one or both sides

Functional description

Personnel: The profile cylinder key is inserted into the profile cylinder. The deadbolt is locked back with the key via a turn (360° rotation). The door can be opened. The door is closed. The deadbolt is locked forward with the key via a turn (360° rotation). The door is fully locked.

Locations

- Passage door
- Technical room
- Sanitary room
- Patient door psychiatry

Technical data

Material	Stainless steel
Surface	Matt
Faceplate dimension [mm]	280 x 30 x 4



Technical data

Forend material	Stainless steel
Material deadbolt	Stainless steel
Lock housing material	Stainless steel
Locking mechanism	prepared for profile half cylinder
Recodability	no
Weight [kg]	2,0
Lock dimensions [mm]	200 x 22 x 220
bolt throw mm	20
external visual indicator	mechanical
Closing processes	500.000
Max. lateral transom load capacity [kN]	50
Relative humidity	95% non-condensing
Relative humidity [%]	95% non-condensing