

## SL profile cylinder food hatch lock with latch bolt

Article No.: SL 201

---

Cam lock for inspection hatches with single-turn cam lock release. In the standard version, the lock has a mechanical external visual indicator on the fitting side.



### Properties

- Easy operation with profile cylinder key (1-turn)
- Pre-equipped for standard Euro profile half cylinders
- Cylinder length depending on door thickness

### Functional description

The profile cylinder key is inserted into the profile cylinder.

The latch bolt is locked back with the profile cylinder key by turning it once (360°). The inspection flap can be opened.

The key can be removed when the latch is locked back and pre-locked.

When the latch bolt is locked, the inspection flap can be quickly closed in an emergency. The latch bolt is automatically secured by the snib.

Type SL 201 is designed for inspection flaps in patient room doors. The latch bolt is locked and unlocked with one turn (360° key rotation). The key can be removed when locked and unlocked.

### Places of use

- Inspection flap

### Technical specifications



## Technical specifications

Material	Stainless steel
Surface	Matt
Face plate dimension [mm]	200 x 30 x 4
Material forend	Stainless steel
Material deadbolt	Stainless steel
Material lock housing	Stainless steel
Lock mechanism	HSL double bit
Levers	7
Recodability	yes
Weight [kg]	1.8
Lock dimensions [mm]	140 x 22 x 135
Closing operations	500,000
Max. lateral bolt load capacity [kN]	50
Relative humidity [%]	95% non-condensing
external visual indicator	mechanically
Latch clearance [mm]	15