Data sheet

SECURITY
MADE IN GERMANY
SINCE 1883

Simplox camlock set 161

Article No.: Simplox 161

Never before has installation in panels and connecting panels been as quick, easy and safe as with the new, patented SIMPLOX. SIMPLOX enables gap-free and bubble-free foam integration into the panel without the need for additional taping. Different sized adapter pins guarantee fast, correct and precise installation and ensure reliable panel ventilation during the foaming process. Experience SIMPLOX now: https://simplox.stuv.de/



Properties

- Polystyrene cassettes
- Zinc-plated steel hooks
- Available with or without filter for ventilation
- Patented ventilation and protective skin
- For hexagon key SW8
- Clamping distance 12 mm
- Span 180°

Functional description

During the foaming process, the new, patented protective skin technology prevents foam from penetrating. After foaming, the self-opening protective skin is simply pierced with an Allen key (optionally available as an accessory). When tightened with the Allen key, the galvanised hook breaks through the protective skin on the side and can be easily swivelled into the cam element. The entire span of the Allen key, from insertion to the end position, is only 180° at most.

Places of use

- Cold room manufacturer
- Refrigerator door manufacturer
- Building components

Technical specifications

Material	Polystyrene
Colour	RAL 9.005
Insert	Width across flat 8
Hole position	closed
Ventilation	yes
Accessories	Strike, adapter pin, operating key, covering caps
Hole spacing [mm]	122
Clamping distance [mm]	12

SECURITY
MADE IN GERMANY
SINCE 1883






Steinbach & Vollmann GmbH | Parkstraße 11 42579 Heiligenhaus | +492056140 | info@stuv.de | www.stuv.de






34
84
38
28,9
161
177,6
161
175
28,5
77,3
23,2