

VARIOFLEX2.KG160.EDG

Article No.: VARIOFLEX2.KG160.EDG

Properties

- 3D adjustability
- Load capacity up to 160 kg
- Opening angle 180°
- Available in different colours
- Available in rising or non rising
- Easy and quick assembly
- Optional: available as a spring variant or with cable entry
- Latching function at 120° (rising version only)
- For doors with an offset of 49 mm or more, centre of rotation 29 mm
- Lift-off version, with anti-lift-out protection (secured second mounting)
- Covering caps with security



Functional description

The Varioflex corner hinge made of stainless steel is ideal for insert parts on heavy doors or doors in very aggressive environments. By using investment casting in stainless steel, we achieve load-bearing capacities of up to 160 kg with increased corrosion resistance. In addition to design elements, you can also choose other functions from the modular system.

Locations

- Cold room manufacturer
- Refrigerated vehicles
- Refrigerated hardware trade
- Metal/door construction

— Refrigerated door manufacturer

Technical data

Load capacity [kg]	up to 160
Offset [mm]	from 49
Material	Stainless steel
Surface	Grinded and blasted
Door version	Right-hand version / left-hand version
Adjustability	3D
Opening angle	180°
Door type	Hinged door
Accessories	Shims
Gradient	Yes / No
Load capacity	up to 160
Offset	from 49
Security	Yes

| SECURITY
| MADE IN GERMANY
| SINCE 1883



| SECURITY
MADE IN GERMANY
SINCE 1883



