

PYLOCK 4011-SB 4011-SB - VdS - 4011-SB - 4011-SB 61,5 mm

4011-SB 4011-SB: PL401X

4011-SB 4011-SB PL4011-SB 4011-SB 4011-SB 4011-SB
4 4011-SB 4011-SB 4 4011-SB 4011-SB 4011-SB 4 4 4011-SB
4011-SB 4011-SB 4011-SB, 4011-SB 4011-SB, 4011-SB
4011-SB 4011-SB 4011-SB 4011-SB. 4011-SB 4011-SB
4011-SB 4011-SB.



4011-SB

- PYLOCK 4011-SB 4011-SB 4 4011-SB 4011-SB
- 4011-SB 4011-SB: 4011-SB 88,3 mm, 4011-SB 61 mm
- 4011-SB 4011-SB PYLOCK 185 mm 4011-SB 255 mm
- 4011-SB 4011-SB 4011-SB 4 4011-SB 4011-SB
- 4011-SB 4011-SB 4 4011-SB 4011-SB 4011-SB 4 4011-SB 4011-SB
- 4011-SB 4011-SB -35°C - + 60°C
- 4011-SB 4011-SB
- 4011-SB 4 4011-SB 4011-SB 4011-SB 4011-SB PIN-4011-SB
- 4011-SB 4011-SB 4011-SB 4011-SB 10 000 4011-SB
- 4011-SB VdS
- 4011-SB 4011-SB 4011-SB 4 4011-SB 4011-SB 4011-SB 4011-SB IP63
- 4011-SB 4011-SB 4011-SB: PL4019 4011-SB-4011-SB, PL4011SBÖ 4011-SB-4011-SB, PL4011-LB
4011-SB 4011-SB 4011-SB

4011-SB 4011-SB

4011-SB 4011-SB PYKEY 4011-SB 4011-SB 4011-SB
4011-SB 4011-SB 4011-SB. 4011-SB 4011-SB, 4
4011-SB 4011-SB 4011-SB 4011-SB 4011-SB. 4011-SB
4011-SB 4011-SB 4011-SB 4 4011-SB 4011-SB 4011-SB
PYKEY. 4011-SB 4011-SB 4011-SB 4011-SB 4011-SB
4011-SB 4011-SB.

4011-SB 4011-SB

Technische Zeichnung des Rohrtresors

Bezeichnung

STUV

Zeichnungsnummer

STUV

Material

STUV

Maße

VdS 2.105:2.013-10VdS 2.110:2.017-09VdS 2.344:2.014-07DIN 14.675 

Material

C:2.003-11

IP 63 / IP 53

Temperaturbereich

-35°C - +60°C

Material

STUV

Material

PYKEY

Material

STUV

Material [mm]

450 mm

Material

STUV

Material

VdS SD1, STUV IV

WebGL

<https://api.sts.sch-server.de/sync/renderings/PYLOCX>

Material [mm]

Rohrtresor/Stuv_Tresorschloss_01.glb
L=88,3 x Ø 61

Material 8x8x8

STUV 88,3 mm, STUV 61 mm

**SECURITY
MADE IN GERMANY
SINCE 1883**



**SECURITY
MADE IN GERMANY
SINCE 1883**

