SECURITY
MADE IN GERMANY
SINCE 1883

PYLOCX Compact [illegible]

[illegible]: PL62XX

[illegible] PYLOCX Compact [illegible], [illegible] [illegible] 30 [illegible] ([illegible]) / 30 [illegible] ([illegible]) [illegible] 60 [illegible] ([illegible]) / 60 [illegible] ([illegible]) ([illegible] 5 [illegible]). [illegible] [illegible] 7,2 [illegible]. [illegible] [illegible] 60 [illegible] [illegible].

[illegible]

- 30 [illegible] / 30 [illegible] [illegible] 60 [illegible] / 60 [illegible]
- [illegible]
- [illegible]
- [illegible]: [illegible] -40 °C [illegible] +60 °C
- [illegible]
- [illegible] [illegible] PIN-[illegible]
- [illegible] [illegible] [illegible] 3000 [illegible]
- [illegible] IP68

[illegible]

[illegible] PYKEY [illegible]. [illegible], [illegible] [illegible]. [illegible].

[illegible]

- Der Doppelzylinder eignet sich für Türen mit Euro-Profilzylinder in technischen oder sicherheitsrelevanten Bereichen wie Infrastruktur-, Technik- oder Versorgungsanlagen. Dank Möglichkeit des Einmalcode-Zugang und Protokollfunktion eignet sich das System besonders für Anwendungen mit wechselnden Zutrittsberechtigungen oder erhöhten Sicherheitsanforderungen..

[illegible]

SECURITY
MADE IN GERMANY
SINCE 1883

[redacted]

[redacted]	[redacted]
[redacted]	[redacted]
[redacted]	[redacted]
[redacted]	[redacted]
[redacted]	IP68
[redacted]	[redacted] 7,2 [redacted]
[redacted]	[redacted] -40 °C [redacted] +60 °C
[redacted]	[redacted]
[redacted]	PYKEY
[redacted]	[redacted]
[redacted]	[redacted]
[redacted]	[redacted]
[redacted] [redacted]	[redacted] (1–2 [redacted]): 30–60 [redacted], [redacted] (3–10 [redacted]): 30–60 [redacted]